

# BOLON FLOORING






# BOLON BY PATRICIA URQUIOLA

## PRODUCT SPECIFICATION

Woven vinyl flooring, product standard EN 1307.

### GENERAL INFORMATION




### ROLLS

	<b>Use classification</b>	EN 1307	33 Heavy
	<b>Weight</b>	ISO 8543	3,1 kg/m <sup>2</sup>
	<b>Thickness</b>	ISO 1765	2,3 mm
	<b>Roll dimension</b>	ISO 24341	2000 mm, 25 m
	<b>Tile dimension</b>	EN ISO 24342	
	<b>Recycled content</b>	ISO 14021	66%




### DURABILITY

	<b>Castor Chair</b>	EN 985	Continuous use
	<b>Colour fastness to light</b>	EN ISO 105-B02	>7
	<b>Dimension stability</b>	ISO 2551 EN 986	Fulfilled

### ACOUSTIC

	<b>Impact sound insulation</b>	EN ISO 10140	9 dB
	<b>Airborne sound absorption</b>	EN ISO 354 $\alpha_w$	0,05
	<b>Airborne sound absorption</b>	EN ISO 354 $\alpha_s$	250 Hz 0,01 500 Hz 0,01 1000 Hz 0,05 2000 Hz 0,09

### ADDITIONAL PROPERTIES

	<b>Anti slip property</b>	DIN 51130	R9
	<b>Pendulum</b>	EN 13036-4	88-93
	<b>Dynamic coefficient of Friction</b>	EN 13893	>0,3
	<b>Body Voltage</b>	EN 1815*	Fulfilled
	<b>Thermal resistance</b>	ISO 8302/ EN 12667	Suitable for underfloor heating

### FIRE PROPERTIES

	<b>Reaction to fire</b>	EN 13501-1	B <sub>fl</sub> -s1
	<b>Critical radiant flux</b>	ASTM E 648	Class 1
	<b>Smoke density</b>	ASTM E 662 Flaming	<450



\* Typical value

# BOLON FLOORING

# BOLON BY PATRICIA URQUIOLA

## CERTIFICATES

For complete information and market specific certificate, visit [bolon.com](http://bolon.com) or contact [sales.support@bolon.com](mailto:sales.support@bolon.com)

		ROLLS
	EN 14041:2004 och EN 14041:2004/AC:2006	0402-CPR-419005
	EN 14041:2004/AC:2006	0086 CPR 770145
<b>LIFE CYCLE PERSPECTIVE</b>		
EPD	ISO 14025 och EN 15804	S-P-03839
Embodied Carbon	EPD modul A1-A3	5,18 kg CO <sub>2</sub> eq.
DGNB Navigator		Yes
GreenTag - GreenRate		Yes
<b>INDOOR AIR</b>		
M1		No
FloorScore		Yes
French VOC		Yes
Rekommenderas av NAAF		Yes
<b>PRODUCT AND RAW MATERIAL</b>		
BASTA		Yes
Byggsvarubedömningen		Yes
ECOproduct		Yes
eBVD		Yes
GBR kretsloppsmärkning		Yes
Best Practice PVC		Yes
GreenTag - PHD		Yes
Declare		Yes



# BOLON

Bolon HQ: Industrivägen 12, 523 90 Ulricehamn, Sweden  
[bolon.com](http://bolon.com) | [info@bolon.com](mailto:info@bolon.com) | [@bolonofficial](https://www.instagram.com/bolonofficial)

March 2025